



Interested in learning  
more about security?

# SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

## Is Internet Explorer More Secure than FireFox?

eb connections. Using this example we discuss best practices in choosing an encryption product (assuming data should be encrypted). We then end with a discussion emphasizing how important it is for security professionals to create a security culture within an organization and how to handle the struggle between usability and security in a real world setting....

Copyright SANS Institute  
Author Retains Full Rights

AD

DEEPARMOR®

Is Internet Explorer More Secure than Firefox?

## **Is Internet Explorer More Secure than FireFox?**

*GIAC Gold Certification*

Author: Lawrence Fortier, 4guys@centurytel.net

Adviser: Jim Purcell

**Outline**

1. Introduction .....	4
2. Demonstration.....	6
3. Discussion .....	8
4. Figures .....	11
5. References .....	14

© SANS Institute 2007, Author retains full rights.

## Abstract

It is common practice to compare web browser security based on known exploits but this paper raises the idea that security is a broader concept and that there are other important issues that need to be considered. In this paper we look at how it is possible to circumvent a company's security policy by using a web browser. Specifically, we compare Internet Explorer with FireFox web browser when connecting to a website that is not FIPS-140 compliant and the companies policy is to use FIPS-140 compliant algorithms for web connections. Using this example we discuss best practices in choosing an encryption product (assuming data should be encrypted). We then end with a discussion emphasizing how important it is for security professionals to create a 'security culture' within an organization and how to handle the struggle between usability and security in a real world setting.

## 1. Introduction

There was a significant increase in the amount of attacks against web applications in 2006 (Symantec Internet Security Threat Report, 2006). The Symantec report states that 7 of every 10 new vulnerabilities were in Web applications. This trend of attackers focusing increasingly on web based attacks, has fueled debate about which Web browser platform is the most secure (Richards, 2005; Yarden, 2004; Faas, 2005; Wildstrom, 2004). This paper will examine how you could put your organization at risk by not using Microsoft Internet Explorer with Microsoft Windows XP Professional SP2 and show that when comparing the security of different web browsers there is more to address than just software security vulnerabilities and exploits.

Internet Explorer is an integral part of Microsoft Windows XP Professional. It is an embedded component of the Windows XP Professional operating system and many windows applications rely on Internet Explorer to function properly. For example, some websites are designed to render properly for Internet Explorer only. More importantly, there are security settings that can be configured in Windows XP Professional to lock down Internet Explorer. These settings can be applied globally using the security configuration manager or with other Microsoft tools.

The security configuration manager allows an administrator to define specific security templates. These templates define a standard configuration for an Operating System which can be applied globally to all Windows XP Professional desktops. This can save time for administrators and, when properly applied, results in a consistent application of security policy throughout an organization.

One of the security settings that can be defined in a security template is the “System cryptology: Use FIPS compliant algorithms for encryption, hashing and signing” (Microsoft, 2005). This is a new setting introduced with windows XP Service Pack 2 (Microsoft, 2005).

When enabled, this setting forces strong encryption to be used by applications needing cryptographic services. Specific applications affected by this setting include Microsoft Internet Information Services (IIS), Microsoft Internet Explorer, Terminal Services, and the Encrypting File system (EFS). In this paper we will examine only the effect on Internet Explorer. When a client attempts to connect to a web server using Internet Explorer with the FIPS setting enabled they are allowed to use the TLS\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA cipher suite only to establish the connection. This setting allows a secure (HTTPS) session to be initiated only if a FIPS 140-2 (Federal Information Processing Standard) approved algorithm for traffic encryption, key exchange, authentication and hashing is also used by the web server.

The National Institute of Standards and Technology (NIST) issues standards and guidelines to aide the Federal Government in the field of computer security (see <http://csrc.nist.gov/publications/fips/index.html> for a listing). These guidelines are referred to as the Federal Information Processing Standards (FIPS). The FIPS 140-2 list security requirements for cryptographic modules. These requirements are created by a group of cryptology experts in the government and private-sector. The National Institute of Standards and Technology recommends enabling the FIPS setting (NIST, 2005).

The Federal government and all its agencies are mandated to use only hardware or software which uses FIPS approved encryption algorithms to comply with regulations. Some websites do not use FIPS approved algorithms to negotiate TLS/SSL connections. What happens when business requirements do not match the security requirements? How does a company decide which cryptographic services they will use to protect the confidentiality, integrity, and availability of their data? In the discussion section we will examine these issues further. For now we will look at how the FIPS security policy affects the two different web browsers when negotiating a connection to a web server that does not support the TLS\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA cipher suite.

### 2. Demonstration

For this demonstration we test a connection to [www.mail.yahoo.com](http://www.mail.yahoo.com) using either Internet Explorer 6 or Mozilla Fire Fox 2.0. This website does not use the TLS\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA cipher suite to negotiate secure connections. Thus we will test site connection success with Firefox 2.0 and Internet Explorer 6.0 with the FIPS setting both enabled and disabled. Wireshark was used to capture the packets for the website connection attempt.

The default setting for Internet Explorer does not have TLS 1.0 checked. For this example this setting was selected and the attempt to connect to [www.mail.yahoo.com](http://www.mail.yahoo.com) was made. Figure 1 displays a portion of the client and server handshake where the SSL protocols are negotiated. You can see that at this point Internet Explorer offered 17 different ciphers to be used to initiate the connection. Ciphers are needed to protect the confidentiality and integrity of the

data while it is in transit, for verification of the server, and possibly for verification of the client. Many ciphers are available to encrypt data and authenticate connections. How do client and server decide which to use? First, the server needs to support the selected cipher. Second, the client generally does not have any control over the protocol that will be used in the session. Thus, trust is given to the web site owner that a secure protocol will be used and that the server will choose the strongest of the clients' available ciphers.

The cipher suite chosen by the server in the aforementioned case was TLS\_RSA\_WITH\_RC4\_128\_MD5. As can be seen in Figure 2, when attempting to connect with FireFox, the client offered 28 different cipher suites to the server. The server and client agreed to use the TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA cipher suite. Both web browsers were able to connect to the web server in this case.

We then tested the connection with the "System cryptology: Use FIPS compliant algorithms for encryption, hashing and signing" security setting enabled. The client portion of the connection for Firefox offered up the same 28 cipher suites and the server used the same TLS\_RSA\_WITH\_AES\_256\_CBC\_SHA cipher suite to negotiate the connection. When trying to connect with Internet Explorer this time, the client only offered up one Cipher suite, the TLS\_RSA\_WITH\_3DES\_EDE\_CBC\_SHA (See Figure 3). This was the result of the security setting forcing the client to use this strong cipher to initiate TLS/SSL connections. However, the web server was not compliant with this cipher and the connection was not established. As can be seen, Firefox was unaffected by the FIPS security setting. This is because Firefox bypassed the enforced security policy of always using FIPS approved cryptographic services for encryption. The user was



able to access the website and presumably would be able to complete their task. If this were a business related task then it would seem that Firefox succeeded where Internet Explorer failed. However the user did not know that by connecting to the website without a FIPS approved algorithm they were actually running afoul of company security policy.

### 3. Discussion

The main thrust of this analysis was the delineation of a specific instance where use of a particular web browser had negative impact on a company's security posture. It was shown how the FireFox web browser ignored a specific security setting that had been enabled in Windows XP Professional. Certainly, given the many security vulnerabilities for Internet Explorer, one must investigate possible alternative software for accessing the World Wide Web. However, as this paper indicates, there are other security issues that need to be taken into account before one reacts by replacing one piece of software for another. The take away message from this paper is that any time we evaluate the security of a certain piece of software we need to be aware of the environment in which the software will be used.

It is very important to have good security policies in place, but there also must be a way to ensure that these policies are being enforced. A policy for approving and testing software is required before it is installed on production systems. It is imperative to know your systems and how the different software applications interact together. Security is full of trade offs. As in the given example, prevention of one type of attack, such as ActiveX exploits, by using

## Is Internet Explorer More Secure than Firefox?

Firefox Browser in place of Internet Explorer opened the door to other potential weaknesses by bypassing company security policy. Unfortunately there are many known flaws with Internet Explorer (Browser helper objects, ActiveX exploits) that need addressing. These vulnerabilities do increase a companies' vulnerability to attack; however, administrators must not create new security risks while trying to fix another.

How can a company decide on an encryption policy that is, what to use and when? This paper discussed how NIST creates standards and certifications that are used by the Federal Government and this may be a good baseline for other companies to use for setting their own policy on which encryption products to use. However, it is also worth noting that not everyone believes in the value of certifying an encryption product. Bruce Schneier, a well-known expert in the field of cryptology, thinks that certification is largely a marketing tool (Salkever, 2002). He believes the true benefit comes when a cryptographic module is open source and that no single company alone can match the power or money that the Government can supply for analysis of Open Source Software (Schneier, 1999). It is from this position that Open Source Software for security becomes the best choice.

So, what happens when business requirements (such as accessing a web site to procure a sole source product) and security requirements (use only FIPS approved algorithms) differ? Should security requirements always trump business requirements in these cases? From a purely technical security standpoint, the answer should be yes. However, if a company cannot do business then there is no need for security. This is the age old standoff between security and business. In real world situations security professionals need to be flexible and must work to

## Is Internet Explorer More Secure than Firefox?

find appropriate alternatives, if in fact the security polices prevent business requirements to be fulfilled. This could help ease tensions between security professionals trying to do their job and business managers and executives trying to do their job.

It is becoming more and more important to create a 'culture of security' in any IT environment whether it is in the Government or Private sector. Each case will be different because there are different individuals who control the process. Some managers will be very aware of how important it is to secure companies data where others will be less so inclined. However, with the costs associated with data storage decreasing more data is being stored for longer periods of time. In order to protect this proliferation of data new regulations are being enacted which hold IT security professionals to a higher standard of accountability than in the past.

2. Figures

© SANS Institute 2007, Author retains full rights.

## Is Internet Explorer More Secure than Firefox?

Figure 1 Wireshark packet capture for Internet Explorer with FIPS setting disabled

```
Secure Socket Layer
SSLv2 Record Layer: Client Hello
  Length: 76
  Handshake Message Type: Client Hello (1)
  Version: SSL 3.0 (0x0300)
  Cipher Spec Length: 51
  Session ID Length: 0
  Challenge Length: 16
  Cipher Specs (17 specs)
    Cipher Spec: TLS_RSA_WITH_RC4_128_MD5 (0x000004)
    Cipher Spec: TLS_RSA_WITH_RC4_128_SHA (0x000005)
    Cipher Spec: TLS_RSA_WITH_3DES_EDE_CBC_SHA (0x00000a)
    Cipher Spec: SSL2_RC4_128_WITH_MD5 (0x010080)
    Cipher Spec: SSL2_DES_192_EDE3_CBC_WITH_MD5 (0x0700c0)
    Cipher Spec: SSL2_RC2_CBC_128_CBC_WITH_MD5 (0x030080)
    Cipher Spec: TLS_RSA_WITH_DES_CBC_SHA (0x000009)
    Cipher Spec: SSL2_DES_64_CBC_WITH_MD5 (0x060040)
    Cipher Spec: TLS_RSA_EXPORT1024_WITH_RC4_56_SHA (0x000064)
    Cipher Spec: TLS_RSA_EXPORT1024_WITH_DES_CBC_SHA (0x000062)
    Cipher Spec: TLS_RSA_EXPORT_WITH_RC4_40_MD5 (0x000003)
    Cipher Spec: TLS_RSA_EXPORT_WITH_RC2_CBC_40_MD5 (0x000006)
    Cipher Spec: SSL2_RC4_128_EXPORT40_WITH_MD5 (0x020080)
    Cipher Spec: SSL2_RC2_CBC_128_CBC_WITH_MD5 (0x040080)
    Cipher Spec: TLS_DHE_DSS_WITH_3DES_EDE_CBC_SHA (0x000013)
    Cipher Spec: TLS_DHE_DSS_WITH_DES_CBC_SHA (0x000012)
    Cipher Spec: TLS_DHE_DSS_EXPORT1024_WITH_DES_CBC_SHA (0x000063)
  Challenge

Secure Socket Layer
SSLv3 Record Layer: Handshake Protocol: Server Hello
  Content Type: Handshake (22)
  Version: SSL 3.0 (0x0300)
  Length: 74
  Handshake Protocol: Server Hello
    Handshake Type: Server Hello (2)
    Length: 70
    Version: SSL 3.0 (0x0300)
    Random.gmt_unix_time: Nov 28, 2006 16:32:58.000000000
    Random.bytes
    Session ID Length: 32
    Session ID (32 bytes)
    Cipher Suite: TLS_RSA_WITH_RC4_128_MD5 (0x0004)
    Compression Method: null (0)
SSLv3 Record Layer: Handshake Protocol: Certificate
  Content Type: Handshake (22)
  Version: SSL 3.0 (0x0300)
```

## Is Internet Explorer More Secure than Firefox?

Figure 2 Wireshark packet capture for Mozilla Firefox with FIPS setting disabled

```
Handshake Protocol: Client Hello
Handshake Type: Client Hello (1)
Length: 171
Version: TLS 1.0 (0x0301)
Random.gmt_unix_time: Dec 31, 1969 18:33:24.000000000
Random.bytes
Session ID Length: 32
Session ID (32 bytes)
Cipher Suites Length: 56
Cipher Suites (28 suites)
Cipher Suite: Unknown (0xc00a)
Cipher Suite: Unknown (0xc014)
Cipher Suite: TLS_DHE_RSA_WITH_AES_256_CBC_SHA (0x0039)
Cipher Suite: TLS_DHE_DSS_WITH_AES_256_CBC_SHA (0x0038)
Cipher Suite: Unknown (0xc00f)
Cipher Suite: Unknown (0xc005)
Cipher Suite: TLS_RSA_WITH_AES_256_CBC_SHA (0x0035)
Cipher Suite: Unknown (0xc007)
Cipher Suite: Unknown (0xc009)
Cipher Suite: Unknown (0xc011)
Cipher Suite: Unknown (0xc013)
Cipher Suite: TLS_DHE_RSA_WITH_AES_128_CBC_SHA (0x0033)
Cipher Suite: TLS_DHE_DSS_WITH_AES_128_CBC_SHA (0x0032)
Cipher Suite: Unknown (0xc00c)
Cipher Suite: Unknown (0xc00e)
Cipher Suite: Unknown (0xc002)
Cipher Suite: Unknown (0xc004)
Cipher Suite: TLS_RSA_WITH_RC4_128_MD5 (0x0004)
Cipher Suite: TLS_RSA_WITH_RC4_128_SHA (0x0005)
Cipher Suite: TLS_RSA_WITH_AES_128_CBC_SHA (0x002f)
Cipher Suite: Unknown (0xc008)
Cipher Suite: Unknown (0xc012)
Cipher Suite: TLS_DHE_RSA_WITH_3DES_EDE_CBC_SHA (0x0016)
Cipher Suite: TLS_DHE_DSS_WITH_3DES_EDE_CBC_SHA (0x0013)
Cipher Suite: Unknown (0xc00d)
Cipher Suite: Unknown (0xc003)
Cipher Suite: SSL_RSA_FIPS_WITH_3DES_EDE_CBC_SHA (0xfeff)
Cipher Suite: TLS_RSA_WITH_3DES_EDE_CBC_SHA (0x000a)

Secure Socket Layer
TLSv1 Record Layer: Handshake Protocol: Server Hello
Content Type: Handshake (22)
Version: TLS 1.0 (0x0301)
Length: 74
Handshake Protocol: Server Hello
Handshake Type: Server Hello (2)
Length: 70
Version: TLS 1.0 (0x0301)
Random.gmt_unix_time: Nov 28, 2006 16:50:52.000000000
Random.bytes
Session ID Length: 32
Session ID (32 bytes)
Cipher Suite: TLS_RSA_WITH_AES_256_CBC_SHA (0x0035)
```

## Is Internet Explorer More Secure than Firefox?

Figure 3 Wireshark packet capture for Internet Explorer with FIPS setting enabled

```
Secure Socket Layer
TLStv1 Record Layer: Handshake Protocol: Client Hello
Content Type: Handshake (22)
Version: TLS 1.0 (0x0301)
Length: 45
Handshake Protocol: Client Hello
Handshake Type: Client Hello (1)
Length: 41
Version: TLS 1.0 (0x0301)
Random.gmt_unix_time: Nov 28, 2006 16:55:59.000000000
Random.bytes
Session ID Length: 0
Cipher Suites Length: 2
Cipher Suites (1 suite)
Cipher Suite: TLS_RSA_WITH_3DES_EDE_CBC_SHA (0x000a)

Secure Socket Layer
TLStv1 Record Layer: Handshake Protocol: Server Hello
Content Type: Handshake (22)
Version: TLS 1.0 (0x0301)
Length: 74
Handshake Protocol: Server Hello
Handshake Type: Server Hello (2)
Length: 70
Version: TLS 1.0 (0x0301)
Page 5
ie2.txt
Random.gmt_unix_time: Nov 28, 2006 16:53:49.000000000
Random.bytes
Session ID Length: 32
Session ID (32 bytes)
Cipher Suite: TLS_RSA_WITH_3DES_EDE_CBC_SHA (0x000a)
```

### 3. References

1. Turner, D. (Ed.). (2006). Symantec Internet Security Threat Report ( ed., Vol. 10). California
2. Richards, Ian (2005). Migrating to Mozilla Firefox: the Pros, Cons & Installation. Retrieved November 22, 2006, from Tech Support Alert Web site:  
<http://www.techsupportalert.com/firefox.htm>
3. Yarden, Jonathan (2005,10 14). Why you should think twice before ditching Internet Explorer. Retrieved November 22, 2006, from Tech Republic Web site:  
<http://articles.techrepublic.com.com/5102-1009-5890288.html>
4. Faas, Dennis (2005, 5 17). Which web browser is the most secure?. Retrieved November 22, 2006, from InfoPackets Web site:  
[http://www.infopackets.com/channels/en/windows/gazette/2005/20050517\\_which\\_web\\_browser\\_is\\_the\\_most\\_secure.htm](http://www.infopackets.com/channels/en/windows/gazette/2005/20050517_which_web_browser_is_the_most_secure.htm)
5. Wildstrom, Stephen H. (2004, 6 29). Internet Explorer Is Just Too Risky. Retrieved November 22, 2006, from BW Online Web site:  
[http://www.businessweek.com/technology/content/jun2004/tc20040629\\_7734\\_tc120.htm](http://www.businessweek.com/technology/content/jun2004/tc20040629_7734_tc120.htm)
6. Microsoft, (2005, 01). System cryptography: Use FIPS compliant algorithms for encryption, hashing, and signing. Retrieved March 23, 2007, from System cryptography: Use FIPS compliant algorithms for encryption, hashing, and signing Web site:  
<http://technet2.microsoft.com/WindowsServer/en/library/6ff574cb-30c4-4ad9-8d5e-ae697c65b9b1033.msp?mfr=true>.



7. Microsoft, (2005, 01). FIPS 140 Evaluation. Retrieved March 23, 2007, from Microsoft TechNet Web site:  
<http://www.microsoft.com/technet/archive/security/topics/issues/fipseval.msp?mfr=true>
8. National Institute of Standards and Technology. (2005). Guidance for Securing Microsoft Windows XP Systems for IT Professionals: A NIST Security Configuration Checklist (NIST Special Publication 800-68). MD: NIST.
9. Salkever, Alex (2002, October 1). Can software security be certified?. Retrieved January 19, 2007, from BW Online Web site:  
[http://www.businessweek.com/technology/content/oct2002/tc2002101\\_6896.htm](http://www.businessweek.com/technology/content/oct2002/tc2002101_6896.htm)
10. Schneier, Bruce (1999, September 15). Crypto-gram newsletter. Retrieved January 19, 2007, from Crypto-Gram: September 15, 1999 Web site:<http://www.schneier.com/crypto-gram-9909.html>



# Upcoming SANS Training

[Click Here for a full list of all Upcoming SANS Events by Location](#)

SANS Seattle 2017	Seattle, WAUS	Oct 30, 2017 - Nov 04, 2017	Live Event
SANS Gulf Region 2017	Dubai, AE	Nov 04, 2017 - Nov 16, 2017	Live Event
SANS Amsterdam 2017	Amsterdam, NL	Nov 06, 2017 - Nov 11, 2017	Live Event
SANS Milan November 2017	Milan, IT	Nov 06, 2017 - Nov 11, 2017	Live Event
SANS Miami 2017	Miami, FLUS	Nov 06, 2017 - Nov 11, 2017	Live Event
SANS Paris November 2017	Paris, FR	Nov 13, 2017 - Nov 18, 2017	Live Event
Pen Test Hackfest Summit & Training 2017	Bethesda, MDUS	Nov 13, 2017 - Nov 20, 2017	Live Event
SANS Sydney 2017	Sydney, AU	Nov 13, 2017 - Nov 25, 2017	Live Event
GridEx IV 2017	Online,	Nov 15, 2017 - Nov 16, 2017	Live Event
SANS San Francisco Winter 2017	San Francisco, CAUS	Nov 27, 2017 - Dec 02, 2017	Live Event
SANS London November 2017	London, GB	Nov 27, 2017 - Dec 02, 2017	Live Event
SIEM & Tactical Analytics Summit & Training	Scottsdale, AZUS	Nov 28, 2017 - Dec 05, 2017	Live Event
SANS Khobar 2017	Khobar, SA	Dec 02, 2017 - Dec 07, 2017	Live Event
SANS Austin Winter 2017	Austin, TXUS	Dec 04, 2017 - Dec 09, 2017	Live Event
SANS Munich December 2017	Munich, DE	Dec 04, 2017 - Dec 09, 2017	Live Event
European Security Awareness Summit & Training 2017	London, GB	Dec 04, 2017 - Dec 07, 2017	Live Event
SANS Bangalore 2017	Bangalore, IN	Dec 11, 2017 - Dec 16, 2017	Live Event
SANS Frankfurt 2017	Frankfurt, DE	Dec 11, 2017 - Dec 16, 2017	Live Event
SANS Cyber Defense Initiative 2017	Washington, DCUS	Dec 12, 2017 - Dec 19, 2017	Live Event
SANS Security East 2018	New Orleans, LAUS	Jan 08, 2018 - Jan 13, 2018	Live Event
SANS SEC460: Enterprise Threat Beta	San Diego, CAUS	Jan 08, 2018 - Jan 13, 2018	Live Event
SANS Amsterdam January 2018	Amsterdam, NL	Jan 15, 2018 - Jan 20, 2018	Live Event
Northern VA Winter - Reston 2018	Reston, VAUS	Jan 15, 2018 - Jan 20, 2018	Live Event
SEC599: Defeat Advanced Adversaries	San Francisco, CAUS	Jan 15, 2018 - Jan 20, 2018	Live Event
SANS San Diego 2017	OnlineCAUS	Oct 30, 2017 - Nov 04, 2017	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced