



Interested in learning
more about security?

SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

Spoofer IP Address Distributed Denial of Service Attacks: Defense-in-Depth

One challenge to businesses worldwide is to permit and even encourage desirable Internet traffic while excluding unwanted or even detrimental traffic. Over the past 18 months, there have been numerous articles, practicals, publications, and white papers written on one particular type of unwanted and detrimental Internet traffic - Distributed Denial of Service (DDoS) attacks. For the Internet community, the key to reducing and/or stopping DDoS attacks is to utilize a defense-in-depth approach without creating limitation...

Copyright SANS Institute
Author Retains Full Rights



AD

Spoofer IP Address Distributed Denial of Service Attacks: Defense-in-Depth

One challenge to businesses worldwide is to permit and even encourage desirable Internet traffic while excluding unwanted or even detrimental traffic. Over the past 18 months, there have been numerous articles, practicals, publications, and white papers written on one particular type of unwanted and detrimental Internet traffic - Distributed Denial of Service (DDoS) attacks.

For the Internet community, the key to reducing and/or stopping DDoS attacks is to utilize a defense-in-depth approach without creating limitations in performance or scalability. The purpose of this paper is to look at a defense-in-depth approach to spoofed IP address DDoS attacks, including known defenses, new techniques, and recent developments.

Introduction

DDoS attacks against e-commerce sites demonstrate the opportunities that attackers now have because of several Internet trends and related factors: a) Attack technology is developing in an open-source environment and is evolving rapidly; b) Increasingly complex software is being written by programmers who have no training in writing secure code and are working in organizations that sacrifice the safety of their clients for speed to market; and c) User demand for new software features instead of safety, coupled with industry response to that demand, has resulted in software that is increasingly supportive of subversion, computer viruses, data theft, and other malicious acts. [1]

Ingress Filtering

DDoS attacks, which have employed forged source addresses, have proven to be a troublesome issue for Internet Service Providers. Ingress filtering is one method to reduce DDoS attacks which use forged IP addresses to be propagated from 'behind' an Internet Service Provider's (ISP) aggregation point. Ingress filtering applies to traffic received at the router from the customer. While ingress traffic filtering reduces the success of source address spoofing, it does not preclude an attacker using a forged source address of another host within the permitted prefix filter range. It does, however, ensure that when an attack of this nature does indeed occur, a network administrator can be sure that the attack is actually originating from within the known prefixes that are being advertised. This simplifies tracking down the culprit, and at worst, an administrator can block a range of source addresses until the problem is resolved. All providers of Internet connectivity are urged to implement ingress filtering to prohibit attackers from using forged source addresses that do not reside within a range of legitimately advertised prefixes. [2]

Ingress Filtering on Cisco Routers

Cisco Systems, the leading manufacturer of backbone routers, provides a Unicast Reverse Path Forwarding (RPF) feature, which helps to reduce problems caused by malformed or forged IP source addresses passing through an ingress router. When Unicast RPF is enabled on a customer interface, the router examines all packets received as input on that interface to make sure that the source address and source interface appear in the routing table and match the interface on which the packet was received. Unicast RPF checks to see if any packet received at a router interface arrives on one of the best return paths to the source of the packet. If the packet was received from one of the best reverse path routes, the packet is forwarded as normal. If there is no reverse path route on the same interface from which the packet was received, it might mean that the source address was modified or forged. If Unicast RPF does not find a reverse path for the packet, the packet is dropped. [3]

Ingress Filtering on Juniper Routers

Juniper Networks, another leading manufacturer of backbone routers, provides a similar inbound packet-filtering feature, filter-source-addr-verification, which accepts only traffic from a customer's network. Applying this filter to the interface attaching the customer will pass traffic only with a valid customer's source IP address; otherwise, it will discard traffic that has an invalid source address. [4]

Ingress Filtering Verification

The Oak Ridge National Laboratory (ORNL), sponsored by the Office of Counter Intelligence of the US Department of Energy, has developed a prototype program that an end-user can run to verify that their ISP has proper ingress filters enabled. The user can download a spoof-tester, which contacts a server with TCP and obtains a spoofed address for testing. The spoof-tester then transmits a series of spoofed packets (TCP, UDP, ICMP) from the user's machine to the server. The server then notifies the spoof-tester if the spoofed packets are detected. (The actual IP address of the user's machine is embedded in the spoofed packets.) If the spoofed packets are detected, the user or testing service could then notify their ISP. (The spoofed packets transport checksums are wrong so there are no packets reflected to the spoofed address.) [5]

Traceback

While ingress filtering deals with dropping malicious packets, it is not likely to completely eliminate the ability to spoof source IP addresses because hosts within customer networks can still disguise themselves as any of the hundreds or thousands of machines in the customer domains. As a result, techniques to

traceback an attack to the source(s) are being developed. Recent proposals for traceback include a variety of packet-marking schemes for routers to use the IPv4 ID field to report information about the edges of the network that the packets traversed. The collective edge information can then be analyzed at the victim to compute the path of the attack. Weaknesses shared by all of the traceback proposals are that the damage done by an attack is not being controlled while the traceback is in progress, and the effectiveness of traceback schemes is reduced as an attack becomes more distributed. However, tracing back an attack to its source is the first step towards the necessary legal actions to discourage such attacks in the future. [6]

Intelligent Network Management/Backbone-Layer Security

Another recent development aimed at stopping DDoS attacks before they reach the customer network is an intelligent network management/backbone-layer security approach. Three companies, Asta Networks, Mazu Networks, and Arbor Networks, appear to take a similar approach, analyzing the patterns of traffic through the routers at the core and edge of the service provider networks, determining whether anomalies in the traffic suggests an attack on a router, server, or other piece of infrastructure is underway, tracing the attack back through the router system if an attack is detected, and then ultimately employing countermeasures against the attack by intelligently dropping packets or throttling back traffic over certain routers. Implementing this kind of distributed approach to detecting and pushing back DDoS attacks would require considerable coordination among the different owners of the networks and routers over which illegitimate traffic might pass. Moreover, the ability to engage in such security without significantly degrading the performance of the networks remains a question. [7]

Egress Filtering

In customer networks, it is customary to create inbound access rules to control what traffic is allowed in from the Internet. All too often however, many administrators pay little attention to what is allowed out of their network. In other words, egress filtering, or the filtering of outbound traffic is not being performed. This can make customer networks an excellent haven for DDoS attacks. The best way to ensure that only assigned IP address space leaves customer networks is to setup an outbound filter on the customers egress router. Besides ensuring that spoofing attacks cannot be launched from a customers network, it's also a great way to insure that private addressing (RFC 1918) is not leaked out. [8]

Egress Filtering on Cisco Routers

Cisco Systems, the leading manufacturer of customer premise equipment (CPE) routers, has outlined a simple and straightforward example for applying outbound filters on CPE routers. [9]

Host-based Defense

Many host computers in user organizations are vulnerable to take-over for DDoS attacks because of inadequate implementation of well-known "best practices", such as those mentioned above. When these computers are used in attacks, the carelessness of their owners is instantly converted to major costs, headaches, and embarrassment for the owners of host computers being attacked. User organizations should check their systems periodically to determine whether they have had malicious software installed, including DDoS Trojan Horse programs. If such software is found, the system should be restored to a known good state. [1]

Host-Based Anti-Tools

One key trend is that DDoS attacks are becoming more prevalent. Additionally, DDoS attack tools are getting more sophisticated and their schemes are getting increasingly more complex. Currently, security experts have identified more than seven DDoS tools and lots of variants are appearing continuously. Knowing the enemy is the first step in stopping DDoS attacks. By having an idea about their tools and methods of attack, the Internet community can get better prepared. A few promising host-based tools that detect DDoS handlers and agents on host systems have been reviewed and are available for free on the Internet. [10]

Recent Developments with Windows XP

In 1981, The Computer Systems Research Group (CSRG), at the University of California at Berkeley, first mated the Unix operating system to the Internet. This was done by implementing Internet protocols and creating a TCP/IP Stack for Unix. The Unix operating system's built-in TCP/IP stack automatically generates and receives Internet plumbing ICMP messages. To facilitate the creation of Internet plumbing applications, such as ping and traceroute, the Berkeley designers allowed programmers to manually generate and receive their own ICMP message traffic. The Berkeley system provides this power through the use of a raw socket. A raw socket short-circuits the TCP/IP stack to open a backdoor directly into the underlying network data transport. This provides full and direct packet level Internet access to any Unix sockets programmer. Beyond their use for supporting simple ping and traceroute, the Berkeley designers intended raw sockets to be used for Internet protocol research purposes only. Because they fully appreciated the inherent danger of abuse of raw sockets, they deliberately denied raw socket access to any applications not running with maximum Unix root privileges. User-level applications were thus prevented from accessing and potentially abusing the raw sockets capability.

Source address spoofing requires root access on Unix systems. The attacker must have root access so that the attack software can open a raw network socket. Most applications use cooked sockets, in which the IP stack provides the necessary packet headers. A raw socket means that the application must prepare the necessary headers itself—that is, do its own cooking. This permits the attacker to put any information he or she wants in the headers, including spoofed source addresses. The most common and familiar DDoS attacks have been generated from Unix-family operating systems. Attacks launched from security-compromised Windows systems are common too. However, the Internet application-programming interface built into Windows prevented attacks from being as damaging as those launched by Unix and Linux systems. The sole reason for this difference was Windows' lack of full raw socket support. Windows Sockets (WinSock) can be readily used for their intended and safe purpose of generating valid ICMP ping and traceroute packets, and application programs are effectively cut off from direct "lower-level" access to the underlying physical Internet. As a result, traditional Windows applications were unable to spoof a machine's IP address to hide the source of any malicious traffic they might generate. However, in Windows XP, Microsoft added a number of powerful networking features because, they say, "Some people complained about Windows lack of full raw socket support". Under the Home Edition of Windows XP, all users are Administrators by default, which means the deliberately restricted raw socket interface has now become available to all system users. [11]

In response to concerns over Microsoft's decision to default all users to full administrative privilege in Windows XP, Steve Gibson and Jeremy Collake developed the SocketToMe and SocketLock programs. SocketToMe is a general-purpose raw socket availability detector. SocketToMe reveals the maximum raw socket access available to programs being executed by the logged on user. Programs may either have no raw socket access, partial (safe) access, or full (unsafe) access. Although SocketToMe can be used alone, it was created for use with the companion SocketLock program. SocketLock modifies the normal privileges of the Windows networking socket system to restrict raw socket access to the system account alone, and all background system processes continue to operate with their traditional full raw socket access, but no users accounts, not even administrators, have any access to raw sockets. Gibson and Collake created the SocketToMe and SocketLock tools to demonstrate the feasibility of implementing a simple alteration in the way Microsoft is going to expose abuse-prone raw sockets to Windows XP users. [12]

Conclusion

Defenses against DDoS attacks depend upon the Internet community working together. With ISP's, customer network administrators, hardware and software

manufacturers, and Internet security professionals implementing defense in depth best practices, together we can reduce and/or hopefully stop DDoS attacks. If you are the victim of a DDoS attack, maintaining logs of events can be very useful to understanding an attack, possibly preventing other attacks, and aiding law enforcement in finding the attacker(s).

References

- [1] Consensus Roadmap for Defeating Distributed Denial of Service Attacks
A Project of the Partnership for Critical Infrastructure Security
http://www.sans.org/ddos_roadmap.htm
- [2] Request for Comments: 2827 Network Ingress Filtering:
Defeating Denial of Service Attacks which employ IP Source Address Spoofing
<http://www.ietf.org/rfc/rfc2827.txt>
- [3] Unicast Reverse Path Forwarding
http://www.cisco.com/univercd/cc/td/doc/product/software/ios111/cc111/uni_rpf.htm
- [4] Minimizing the Effects of DoS Attacks
http://arachne3.juniper.net/techcenter/app_note/350001.html
- [5] Backtracking Spoofed Packets
<http://www.epm.ornl.gov/~dunigan/oci/bktrk.html>
- [6] Steven M. Bellovin – Papers
<http://www.research.att.com/~smb/papers/>
- [7] Recent Developments and Emerging Defenses to DDoS
<http://www.sans.org/infosecFAQ/DNS/developments.htm>
- [8] Egress Filtering v 0.2
<http://www.sans.org/y2k/egress.htm>
- [9] Strategies to Protect Against Distributed Denial of Service (DDoS) Attacks
<http://www.cisco.com/warp/public/707/newsflash.html>
- [10] Understanding DDOS Attack, Tools and Free Anti-tools with Recommendation
http://www.sans.org/infosecFAQ/threats/understanding_ddos.htm
- [11] Why Windows XP will be the DOS Exploitation Tool of Choice
<http://grc.com/dos/winxp.htm>
- [12] Windows XP Home Edition Must be Made More Secure
<http://grc.com/dos/sockettome.htm>



Upcoming SANS Training

[Click Here for a full list of all Upcoming SANS Events by Location](#)

SANS Chicago 2017	Chicago, ILUS	Aug 21, 2017 - Aug 26, 2017	Live Event
SANS Virginia Beach 2017	Virginia Beach, VAUS	Aug 21, 2017 - Sep 01, 2017	Live Event
SANS San Francisco Fall 2017	San Francisco, CAUS	Sep 05, 2017 - Sep 10, 2017	Live Event
SANS Tampa - Clearwater 2017	Clearwater, FLUS	Sep 05, 2017 - Sep 10, 2017	Live Event
SANS Network Security 2017	Las Vegas, NVUS	Sep 10, 2017 - Sep 17, 2017	Live Event
SANS Dublin 2017	Dublin, IE	Sep 11, 2017 - Sep 16, 2017	Live Event
SANS Baltimore Fall 2017	Baltimore, MDUS	Sep 25, 2017 - Sep 30, 2017	Live Event
Data Breach Summit & Training	Chicago, ILUS	Sep 25, 2017 - Oct 02, 2017	Live Event
SANS Copenhagen 2017	Copenhagen, DK	Sep 25, 2017 - Sep 30, 2017	Live Event
SANS London September 2017	London, GB	Sep 25, 2017 - Sep 30, 2017	Live Event
Rocky Mountain Fall 2017	Denver, COUS	Sep 25, 2017 - Sep 30, 2017	Live Event
SANS SEC504 at Cyber Security Week 2017	The Hague, NL	Sep 25, 2017 - Sep 30, 2017	Live Event
SANS DFIR Prague 2017	Prague, CZ	Oct 02, 2017 - Oct 08, 2017	Live Event
SANS Oslo Autumn 2017	Oslo, NO	Oct 02, 2017 - Oct 07, 2017	Live Event
SANS October Singapore 2017	Singapore, SG	Oct 09, 2017 - Oct 28, 2017	Live Event
SANS AUD507 (GSNA) @ Canberra 2017	Canberra, AU	Oct 09, 2017 - Oct 14, 2017	Live Event
SANS Phoenix-Mesa 2017	Mesa, AZUS	Oct 09, 2017 - Oct 14, 2017	Live Event
Secure DevOps Summit & Training	Denver, COUS	Oct 10, 2017 - Oct 17, 2017	Live Event
SANS Tysons Corner Fall 2017	McLean, VAUS	Oct 14, 2017 - Oct 21, 2017	Live Event
SANS Brussels Autumn 2017	Brussels, BE	Oct 16, 2017 - Oct 21, 2017	Live Event
SANS Tokyo Autumn 2017	Tokyo, JP	Oct 16, 2017 - Oct 28, 2017	Live Event
SANS Berlin 2017	Berlin, DE	Oct 23, 2017 - Oct 28, 2017	Live Event
SANS Seattle 2017	Seattle, WAUS	Oct 30, 2017 - Nov 04, 2017	Live Event
SANS San Diego 2017	San Diego, CAUS	Oct 30, 2017 - Nov 04, 2017	Live Event
SANS Gulf Region 2017	Dubai, AE	Nov 04, 2017 - Nov 16, 2017	Live Event
SANS Miami 2017	Miami, FLUS	Nov 06, 2017 - Nov 11, 2017	Live Event
SANS Amsterdam 2017	Amsterdam, NL	Nov 06, 2017 - Nov 11, 2017	Live Event
SANS Milan November 2017	Milan, IT	Nov 06, 2017 - Nov 11, 2017	Live Event
SANS Sydney 2017	Sydney, AU	Nov 13, 2017 - Nov 25, 2017	Live Event
Pen Test Hackfest Summit & Training 2017	Bethesda, MDUS	Nov 13, 2017 - Nov 20, 2017	Live Event
SANS Paris November 2017	Paris, FR	Nov 13, 2017 - Nov 18, 2017	Live Event
SANS Adelaide 2017	OnlineAU	Aug 21, 2017 - Aug 26, 2017	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced