



Interested in learning
more about security?

SANS Institute InfoSec Reading Room

This paper is from the SANS Institute Reading Room site. Reposting is not permitted without express written permission.

Wireless Application Protocol 2.0 Security

This paper will focus on WAP 2.0, how it differs from previous versions of WAP and how these differences impact on security. It will assume the reader has previous knowledge of WAP 1.x, which has already been detailed in earlier SANS documents (for example, [SANS-A], [SANS-B], [SANS-C] and [SANS-D]), and will begin by summarizing current WAP 1.x security mechanisms.

Copyright SANS Institute
Author Retains Full Rights

AD

DEEPARMOR®

Wireless Application Protocol 2.0 Security

Tamzin C Jeffs

November 2001

© SANS Institute 2001, Author retains full rights

SANS GEAC Security Essentials Certification (GSEC) Practical Assignment


Introduction

During recent years the Internet and wireless voice communications have undergone wide and rapid acceptance. The Internet has proved to be an easy and efficient way of delivering services to millions of wired users. Mobile phones are equally efficient at providing remote services. It was then only a question of time before these two technologies would begin to converge, to bring the convenience of the Internet to the wireless community.

The mobile phone market has grown ten-fold from 1994 to 1999, from 26 million units to 278 million units. Personal computers doubled in the same period. There are now more mobile phones sold annually than PCs and TVs combined [GOLD-A]. The communications industry is fast recognising that the future of e-commerce lies in networked computing from the mobile phone.

Current projections indicate that there will be 1.5 billion mobile subscribers by 2006, 684 million of which will use microbrowser¹-enabled services. This compares with 500 million desktop or laptop Internet users. By 2006, 82% of the installed base will be microbrowser-enabled, but not all will be used [OVUM-A]. See the figure below for the forecasted trends from now to 2006.

Figure 1. Forecast for cellular subscribers, microbrowser-enabled handsets and active microbrowser users (2000 to 2006)



¹ Software that allows the user to access the Internet from a mobile device.

The major problem with converging these technologies is the difference in device structure and network properties. Internet access is generally obtained via a desktop or laptop and this will be replaced by a smaller wireless device. This has limited display capabilities, limited input facilities, limited memory and CPU, plus limited battery power. In addition the wireless network, compared to the wired network, has lower bandwidth that can cause poor performance, high latency and less connection stability.

In order to address these issues, the WAP Forum² has introduced a standardised way to provide communication between the wired and wireless worlds. The phenomenal growth in wireless web phones, personal digital assistants and other handheld devices, together with strong demand for mobile Internet services, have provided the momentum behind Wireless Application Protocol ('WAP').

WAP is optimised for small devices and is based on the Internet client/server architecture. Essentially, it is the mobile equivalent of traditional Internet protocols, but with adaptations to the bounds of the wireless network and the wireless device. It is bearer-independent and supports the major operating systems used in handheld devices (including Epoc, JavaOS, PalmOS and Windows CE).

The WAP Forum released WAP 1.1 in June 1999 and WAP 1.2 was ratified in December 1999. The next generation WAP, WAP 2.0 (also known as WAP-NG), was released for public review on 1 August 2001. WAP 2.0 continues the standard's convergence with Internet technology and is based on the Internet Engineering Task Force ('IETF') standard of TCP/IP and the World Wide Web Consortium's ('W3C') recommendation of XHTML³. It also improves the user experience through additional features, such as Data Synchronization (Sync ML), Multimedia Messaging Service, Persistent Storage Interface, Provisioning, Pictograms and an evolved version of WAP Push [WAPF-A].

This paper will focus on WAP 2.0, how it differs from previous versions of WAP and how these differences impact on security. It will assume the reader has previous knowledge of WAP 1.x, which has already been detailed in earlier SANS documents (for example, [SANS-A], [SANS-B], [SANS-C] and [SANS-D]), and will begin by summarising current WAP 1.x security mechanisms.

² The WAP Forum is an industry association of wireless device manufacturers, service providers and software companies. It was founded in 1997 by three mobile phone manufacturers (Ericsson, Motorola and Nokia), together with the US software company Phone.com (formerly Unwired Planet).

³ eXtensible HyperText Markup Language ('XHTML').

WAP 1.1 security

The main security initiative in WAP 1.1 is the Wireless Transport Layer Security protocol ('WTLS'). WTLS provides similar functionality to that of the Internet's transport layer security v1.0 protocol ('TLS'), the IETF's standard for securing Internet browsing, and this, in turn, is based on Secure Sockets Layer ('SSL') v3.0 Internet protocol.

However, compared to traditional TLS/SSL, WTLS provides faster algorithm processing (by minimising protocol overheads), enables more data compression and provides the added functionality of datagram support⁴, optimised handshake⁵ and dynamic key refreshing.

WTLS provides a robust, efficient basis for secure transactions and supports data integrity, authentication and privacy services between communicating applications [WAPF-D]. A summary of each security service and the corresponding WTLS security mechanism is outlined in the table below.

Security requirement	Security mechanism
Confidentiality/privacy	■ Secret key cryptography using bulk ciphers, such as RC5_CBC, DES_CBC, 3DES_CBC, IDEA
Authentication/authorisation and non-repudiation	■ Public key cryptography using key exchange suites, such as RSA, Diffie-Hellman, Elliptic Curve Diffie-Hellman
Integrity	■ MACs - HMAC based (for example SHA-1, MD5) or XOR based (for example SHA-1)

⁴ TLS/SSL cannot operate over UDP, whereas WTLS can.

⁵ For optimised handshakes, in contrast to the full handshake, the server obtains the client certificate from a certificate distribution service or from its own source, without requesting it over the air from the client.

WAP 1.2 security

To address the lack of both non-repudiation services and real end-user authentication in WAP 1.1, the WAP Forum introduced two new initiatives in WAP 1.2:

- the WMLScript Crypto Library – provides application layer security by the use of WMLScript applets to enable cryptographic signing of WML content. These applets run on the client and are stored within a WMLScript Crypto library; and
- the WAP Identity Module ('WIM') - 'a tamper-resistant⁶ device which is used in performing WTLS and application level security functions, and especially, to store and process information needed for user identification and authentication' [WAPF-B].

These two initiatives are supported by a wireless Public Key Infrastructure ('PKI'), which provides the functions that store and process information needed for user identification and authentication [WAPF-B].

WAP 2.0 security

A much publicised criticism of WAP 1.x, and a primary cause of reluctance to adopt the protocol, is the lack of end-to-end security or end-to-end authentication. This is due to the presence of a WAP gateway, which effectively acts as a bridge between the mobile and IP networks. The gateway is the single point of translation between the WAP and standard Internet protocols (WTLS and TLS/SSL) and markup languages (WML⁷/WMLScript⁸ and HTML⁹/JavaScript). As part of the translation process, data is momentarily present in plaintext and it is this 'gap' in security that can, potentially, pose a serious security risk.

In an attempt to reduce this risk, gateway operators claim to take precautions to ensure plaintext is never written to disk, decryption and re-encryption takes place in the volatile, internal memory and is erased as quickly as possible, the gateway is physically secured and administrative access to the gateway is limited. However, the residual risk may still be too unacceptable for services that require secure transactions, such as banking and brokerage.

Alternatively, vendors with strenuous security requirements could host their own gateway. This would be within the vendor's own network environment and

⁶ Tamper-resistant means that certain physical hardware protection is used, which makes it unfeasible to extract or modify information in the module (volatile, non-volatile memory and other parts) [WAPF-B]

⁷ Wireless Markup Language ('WML').

⁸ Wireless Markup Language Script ('WMLScript').

⁹ Hyper Text Markup Language ('HTML').

would be under their control and security measures. Data, encrypted by WTLS, would pass directly between the client and the vendor's gateway and would then pass through the vendor's network to their web server. This would, effectively, provide a form of end-to-end security. However, in practice this is a very large overhead for vendors. Also, the majority of WAP phones are sold with the mobile operator's gateway setting pre-loaded. It can be complicated and frustrating exercise to change that setting and some operators prevent users from accessing any gateway other than their own.

WAP 2.0 addresses the lack of end-to-end security by introducing support and services for Internet protocols (including TCP/IP¹⁰, TLS and HTTP¹¹) into the WAP environment. Internet protocols can, therefore, be used directly between the client and wireless network and this eliminates the need for protocol translation at the WAP gateway. In doing so, this effectively provides transport level end-to-end security.

WAP 2.0 architecture

In the previous versions of the WAP specification, a new set of protocols, collectively known as WAP 1.x stack, were created to facilitate the transfer of data along low-bandwidth mobile networks to constrained devices. With the emergence of high-speed wireless networks (for example, 2.5G and 3G) and improvements in device technology, appropriate IP connectivity can now be achieved between the device and wireless network. WAP 2.0 takes advantage of this by introducing Internet protocols directly into the WAP environment.


The previous WAP 1.x stack and proposed WAP 2.0 stacks are detailed in figure 2 overleaf.

Note the use of a WAP 'proxy', to replace the gateway in WAP 2.0. This is not used for translation, merely as a conduit to optimise the communications process and perhaps offer mobile service enhancements, such as location-based services. A proxy is also required to enable 'push' capabilities.

¹⁰ Transmission Control Protocol/Internet Protocol ('TCP/IP').

¹¹ HyperText Transfer Protocol ('HTTP').

Figure 2. WAP 1.x stack versus WAP 2.0 stack



The WAP 2.0 stack essentially replaces the four layers beneath the Wireless Application Environment ('WAE') of the WAP 1.x stack as follows (see figure 3 overleaf):

HTTP

- replaces the wireless session protocol ('WSP') and wireless transaction protocol ('WTP'); and
- supports HTTP request/response transactions, response message body compression and the establishment of secure tunnels.


TLS/SSL

- replaces wireless transport layer security ('WTLS'); and
- supports secure transactions with cipher suites, certificate formats, signing algorithms and the use of session resume.

TCP

- replaces wireless datagram protocol ('WDP'); and
- provides connection-oriented services.

Figure 3. Internet and WAP protocol stacks



It is important to note that HTTP, TLS and TCP protocols are not identical to the Internet versions as they are 'wireless profiled'. This means they have been optimised for wireless environments and can interoperate with the standard implementations in the Internet [WAPF-C].

The 'profiled' TLS specification use similar security mechanisms/algorithms to those listed previously for WTLS:

- MACs to carry out message integrity checks (supports the common MAC algorithms SHA-1 and MD5)
- public key cryptographic authentication of the client and server (be it origin or proxy), either through the use of certificates or anonymously (supports the use of RSA, Diffie-Hellman and Elliptic Curve Cryptography algorithms); and
- message confidentiality is protected by secret key cryptography (using DES, triple DES, RC5 and IDEA algorithms).

The WAE, nominally viewed as the 'WAP browser', has evolved in WAP 2.0 to embrace developing standards for Internet browser markup language [WAPF-A]. WAP 1.x uses the lightweight markup language WML (which is a subset of XML¹² and is similar to the Internet's HTML, but optimised for use in handheld mobile devices). WAP 2.0 introduces WML2, which is based on the basic profile of XHTML, developed by the W3C to replace and enhance the HTML language commonly used today. This will eventually enable developers to write applications for both PC and WAP clients using a common subset of language elements and development tools.

Conclusion

WAP 2.0 continues to support the original WAP 1.x stack and, by encompassing both stacks, provides backwards compatibility. Although this has the advantage of enabling connectivity over a broader range of networks and wireless bearers, the wireless environment is now exposed to security issues related to the Internet protocols as well as those related to WAP 1.x and the WAP 1.x architecture.

Some of the weaknesses in WTLS are also present in the current TLS/SSL used over the Internet, and will therefore also apply to the 'profiled' TLS used by WAP 2.0. These include: no obligation to exchange certificates; no obligation to verify certificates and authenticate owners; and the permitting of anonymous Diffie-Hellman mode (where exchanges are not supported by public key certificates) and may allow man-in-the-middle attacks (where an attacker is able to substitute his own public key for the requested public key).

Therefore, some of the old security issues will still remain in WAP 2.0. However, WAP 2.0 does address arguably the largest barrier to WAP's use and acceptance, the 'gap' in security caused by protocol translation at the gateway. There will, no doubt, also be the introduction of new security threats and issues to the wireless environment as it continues its convergence with the Internet.

¹² Extensible Markup Language ('XML').

References

- IMBA-A Durham-Vichr, Deborah & Getgen, Kimberly (2001), 'WAP 2.0 – Securing the Internet Without Wires', IBM, August 2001.
URL: <http://www-106.ibm.com/developerworks/wireless/library/wi-sectrends/>
- GOLD-A Kramer, R & Simpson, B (1999) – 'Wireless Wave II – The Data Wave Unplugged', Goldman Sachs Investment Research, 10 November 1999.
URL: <http://www.gs.com>
- OVUM-A MacKenzie, M & O'Loughlin, MA (2000) – 'WAP Market Strategies', Press White Paper, Ovum, May 2000. URL: <http://www.ovum.com>
- SANS-A Laquina, S (2000), 'Wireless Application Protocol', SANS Information Security Reading Room, 4 September 2000.
URL: <http://www.sans.org/infosecFAQ/wireless/WAP2.htm>
- SANS-B Schramm, J (2000), 'Security Issues in WAP and I-Mode', SANS Information Security Reading Room, 2 December 2000.
URL: <http://www.sans.org/infosecFAQ/wireless/WAP4.htm>
- SANS-C Cutts, M (2000), 'Secure Wireless Application Protocol (WAP) on the Enterprise, Ready or Not?', SANS Information Security Reading Room, 5 September 2000.
URL: http://www.sans.org/infosecFAQ/wireless/WAP_enterprise.htm
- SANS-D Combs, J (2000), 'Security Models for M-Commerce', SANS Information Security Reading Room, 20 December 2000.
URL: <http://www.sans.org/infosecFAQ/wireless/models.htm>
- WAPF-A WAP Forum (2001), 'Wireless Application Protocol WAP 2.0 Technical White Paper', August 2001. URL: <http://www.wapforum.org>
- WAPF-B WAP Forum (2001), 'Wireless Application Protocol Architecture Specification', WAP-210-WAPArch-20010712-a, 12 July 2001.
URL: <http://www.wapforum.org>
- WAPF-C WAP Forum (2001), 'Wireless Application Protocol Wireless Profiled TCP', WAP-225-TCP-20010331-a, 31 March 2001.
URL: <http://www.wapforum.org>
- WAPF-D WAP Forum (2001), 'Wireless Application Protocol Wireless Transport Layer Security', WAP-261-WTLS-20010406-a, 6 April 2001.
URL: <http://www.wapforum.org>
- WAPF-E WAP Forum (2000), 'WAP Identity Module Specification', WAP-198-WIM, 18 February 2000. URL: <http://www.wapforum.org>



Upcoming SANS Training

[Click Here for a full list of all Upcoming SANS Events by Location](#)

SANS Las Vegas 2018	Las Vegas, NVUS	Jan 28, 2018 - Feb 02, 2018	Live Event
Cyber Threat Intelligence Summit & Training 2018	Bethesda, MDUS	Jan 29, 2018 - Feb 05, 2018	Live Event
SANS Miami 2018	Miami, FLUS	Jan 29, 2018 - Feb 03, 2018	Live Event
SANS London February 2018	London, GB	Feb 05, 2018 - Feb 10, 2018	Live Event
SANS Scottsdale 2018	Scottsdale, AZUS	Feb 05, 2018 - Feb 10, 2018	Live Event
SANS SEC455: SIEM Design Beta One 2018	Arlington, VAUS	Feb 12, 2018 - Feb 13, 2018	Live Event
SANS Southern California- Anaheim 2018	Anaheim, CAUS	Feb 12, 2018 - Feb 17, 2018	Live Event
SANS Secure India 2018	Bangalore, IN	Feb 12, 2018 - Feb 17, 2018	Live Event
SANS Brussels February 2018	Brussels, BE	Feb 19, 2018 - Feb 24, 2018	Live Event
SANS Secure Japan 2018	Tokyo, JP	Feb 19, 2018 - Mar 03, 2018	Live Event
Cloud Security Summit & Training 2018	San Diego, CAUS	Feb 19, 2018 - Feb 26, 2018	Live Event
SANS Dallas 2018	Dallas, TXUS	Feb 19, 2018 - Feb 24, 2018	Live Event
SANS New York City Winter 2018	New York, NYUS	Feb 26, 2018 - Mar 03, 2018	Live Event
CyberThreat Summit 2018	London, GB	Feb 27, 2018 - Feb 28, 2018	Live Event
SANS London March 2018	London, GB	Mar 05, 2018 - Mar 10, 2018	Live Event
SANS Secure Singapore 2018	Singapore, SG	Mar 12, 2018 - Mar 24, 2018	Live Event
SANS Secure Osaka 2018	Osaka, JP	Mar 12, 2018 - Mar 17, 2018	Live Event
SANS Paris March 2018	Paris, FR	Mar 12, 2018 - Mar 17, 2018	Live Event
SANS San Francisco Spring 2018	San Francisco, CAUS	Mar 12, 2018 - Mar 17, 2018	Live Event
SANS Northern VA Spring - Tysons 2018	McLean, VAUS	Mar 17, 2018 - Mar 24, 2018	Live Event
SANS Secure Canberra 2018	Canberra, AU	Mar 19, 2018 - Mar 24, 2018	Live Event
SANS Munich March 2018	Munich, DE	Mar 19, 2018 - Mar 24, 2018	Live Event
SANS Pen Test Austin 2018	Austin, TXUS	Mar 19, 2018 - Mar 24, 2018	Live Event
ICS Security Summit & Training 2018	Orlando, FLUS	Mar 19, 2018 - Mar 26, 2018	Live Event
SANS Boston Spring 2018	Boston, MAUS	Mar 25, 2018 - Mar 30, 2018	Live Event
SANS 2018	Orlando, FLUS	Apr 03, 2018 - Apr 10, 2018	Live Event
SANS Abu Dhabi 2018	Abu Dhabi, AE	Apr 07, 2018 - Apr 12, 2018	Live Event
Pre-RSA® Conference Training	San Francisco, CAUS	Apr 11, 2018 - Apr 16, 2018	Live Event
SANS London April 2018	London, GB	Apr 16, 2018 - Apr 21, 2018	Live Event
SANS Zurich 2018	Zurich, CH	Apr 16, 2018 - Apr 21, 2018	Live Event
SANS Baltimore Spring 2018	Baltimore, MDUS	Apr 21, 2018 - Apr 28, 2018	Live Event
SANS Dubai 2018	OnlineAE	Jan 27, 2018 - Feb 01, 2018	Live Event
SANS OnDemand	Books & MP3s OnlyUS	Anytime	Self Paced